

# **BDS2544 WALL-MOUNT PLATE INSTALLATION**

**(FOR BDS-2541, BDS-2543 LEFT/RIGHT DUO REAR DELIVERY UNITS)**

**TOOLS REQUIRED:** HAND DRILL, 5/32" DIAMETER DRILL BIT, 1/2" WRENCH,  
AND LUBRICANT FOR LAG-SCREWS (SOAP WORKS WELL).

**MATERIALS REQUIRED (ALL PROVIDED):** 1-BDS2544 WALL MOUNT, 4-5/16" FLAT WASHERS, 4-5/16"X 3"L LAG SCREWS

## **INSTRUCTIONS FOR A WOODEN STUD WALL CONSTRUCTION:**

- 1) LOCATE THE WALL STUDS IN THE AREA YOU WANT THE WALL-MOUNT PLATE, AND MARK THE CENTER OF THE TWO STUDS ONTO WHICH YOU WILL ATTACH THE WALL-MOUNT PLATE.
- 2) WITH A PENCIL, DRAW A HORIZONTAL LINE 12 5/8" ABOVE THE FINISHED FLOOR (USE A LEVEL TO ENSURE PROPER INSTALLATION). ALIGN THE BDS2544 WALL-MOUNT'S BOTTOM EDGE WITH THIS LINE, AND POSITION THE WALL-MOUNT SO THE LAG-SCREW HOLES ARE CENTERED UPON THE WALL STUDS. (SEE **SKETCH BELOW** FOR PROPER ORIENTATION)
- 3) WITH A PENCIL, TRANSFER THE FOUR SCREW HOLE LOCATIONS TO THE WALL.
- 4) PRE-DRILL THESE HOLES WITH THE 5/32" DIAMETER DRILL.
- 5) LUBRICATE THE FOUR LAG-SCREWS WITH LUBRICANT (SOAP MAY BE USED).
- 6) POSITION THE WALL-MOUNT PLATE AS SHOWN IN THE **SKETCH BELOW**, AND FASTEN THE PLATE TO THE WALL WITH THE PROVIDED LAG-SCREWS (USE THE 5/16" FLAT WASHERS WITH THE LAG-SCREWS).

## **INSTRUCTIONS FOR METAL STUD WALL CONSTRUCTION:**

**NOTE: METAL STUDS WILL NOT ADEQUATELY SECURE THE WALL-MOUNT. THE WALL WILL NEED TO BE STRENGTHENED WITH WOOD FRAMING BEFORE INSTALLATION CAN PROCEED.**

**\*\*THE PROVIDED LAG BOLTS NEED TO BE SCREWED INTO WOODEN FRAMING\*\***

